

ORIA

MANUFACTURER

Thrislington Cubicles, Prince William Avenue, Deeside, Flintshire, CH5 2QZ.

T: +44 (0)1244 520 677 F: +44 (0)1244 535 670

E: info@thrislingtoneducation.com

13mm Corian solid surface from standard range of colours, with 18mm moisture resistant mdf substrate. Sited 870mm from f.f.l, 500mm deep with profiled 100mm thermoformed recess and integrated wastes. Corian splashback 150mm tall to finish flush with rear of trough.

SUPPORT FRAMEWORK

Cantilevered galvanised steel support arms connected to 2.5mm thick full length channel sub frame, fixed to existing structure, using appropriate fixings.

PANELS

15mm moisture resistant chipboard faced with specified high pressure laminate finish and edged with matching tape/laminate. Alternatively, vertical edges can be postformed. All panels are lift off and fixed with male plastic keku clips fixed to rear, to interface with matching female keku clip, fixed to vertical infill.

INFILLS

Vertical infill's manufactured from 15mm moisture resistant chipboard/mdf core, faced with specified high pressure laminate; grooved to accept a female keku clip, plywood skirting to accept appropriate floor finish

FINISHES

Top Colour: 0.7mm HP Laminate from standard colour range.

Panel Colour: 12mm Compact Grade Laminate from standard colour range. Vertical Infill Colour: 0.7mm HP Laminate from standard colour range.

