

K32

POLO TALL

MANUFACTURER

Thrislington Cubicles, Prince William Avenue, Deeside, Flintshire, CH5 2QZ.

T: +44 (0)1244 520 677

F: +44 (0)1244 535 670

E: info@thrislingtoneducation.com

SPECIFICATION

Overall standard cubicle height: 2400mm with 23mm floor clearance.

FRAMEWORK

Full aluminium frame. Extruded aluminium headrail and vertical posts. Lock locates directly into vertical post section.

DOOR

15mm moisture resistant high-density chipboard core, faced with high pressure laminate and edged with 2mm pvc tape. Supported on powder coated aluminium foot, with height adjustment, incorporating rise and fall closing mechanism. Pivots between foot and aluminium headrail, with anti finger trap clearance on pivot side of door.

DIVIDER

15mm moisture resistant high-density chipboard core, faced with high pressure laminate and edged with 2mm pvc tape. Through fixed into floor mounted powder coated aluminium channel.

FITTINGS

Painted aluminium lock, which locates directly into aluminium framework, with emergency release facility. Incorporating solid aluminium bar, with replaceable hard nylon shear tip and emergency release facility. Extruded aluminium brackets with allen key head through fixings for all wall, door, division and panel fixings.

FINISHES

Aluminium: Dark (RAL 7011) or light (RAL 7035) grey powder coated.

Door: 0.8mm HP Laminate from standard colour range.

Divider: 0.8mm HP Laminate from standard colour range.

Edge trim: 2mm heat bonded pvc, colour to be specified.

Foot and lock: Dark (RAL 7011) or Light (RAL 7035) grey powder coated.

Edge: Polished.



thrislington cubicles

THRISLINGTON CUBICLES T +44 (0)1244 520 677
PRINCE WILLIAM AVENUE F +44 (0)1244 535 670
SANDYCROFT DEESIDE E EDU@THRISLINGTONEDUCATION.COM
FLINTSHIRE CH5 2QZ WWW.THRISLINGTONEDUCATION.COM